



TEXTILNÍ ZKUŠEBNÍ ÚSTAV, s.p.
(TEXTILE TESTING INSTITUTE)

Notified body No. 1021

Cejl 480/12, Zábřovice, 603 00 Brno, Czech Republic



issues

CERTIFICATE OF CONSTANCY OF PERFORMANCE

No. 1021 - CPR – 010-1/16

In compliance with Regulation No. 305/2011 (EU) of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products (Construction Products Regulation – CPR), in valid wording, Annex V, art. 1.2 b)

Textile floor coverings: Product group 5B - PA-ECT350

Material:	100% polyamide
Primary backing:	polyester
Secondary backing:	felt – Ecotrust 350
Technology:	tufted – cut pile/ tufted – loop pile/ woven – loop pile

Products placed on the market under the name or trade mark of:

Manufacturer: **Ege Carpets A/S**
Industrivej Nord 25, DK-7400 Herning, Denmark
ID: CVR 38454218

Manufacture location: 1) Ege Carpets A/S - Industrivej Nord 25, DK-7400 Herning, Denmark
2) Ege Carpets A/S - Industrivej 3, DK-6510 Gram, Denmark

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard:

EN 14041:2004/ AC:2006 Resilient, textile and laminate floor coverings – Essential characteristics

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.


Products fulfil the essential characteristic of reaction to fire: **Class B_{fl} – s1**

The present certificate was issued on the basis of the protocol No. 1021/16/033 (22.02.2016), No. 1021/16/187 (15.08.2016), No. 1021/17/006 (11.01.2017), No. 1021/16/033/K1 (03.03.2017), No. 1021/17/244 (18.08.2017), No. 1021/17/308 (03.11.2017), No. 1021/18/071 from 13.04.2018, No. 1021/18/250 (04.10.2018), No. 1021/18/301 (05.11.2018), No. 1021/20/022 (10.01.2020), No. 1021/20/305 (03.09.2020), No. 1021/22/121 (31.05.2022) and No. 1021/23/075 (06.03.2023) issued by NB 1021 TZU Brno. Detailed description of product group is stated in Annex No. 1 of the certificate.

This certificate was first issued on February 22, 2016 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.



Brno, 06.03.2023



RNDr. Pavel Malčík
Managing Director

TEST REPORTS and DOCUMENTATION:

<i>Product</i>	<i>Test report</i>	<i>Date</i>	<i>Accredited laboratory</i>	<i>Product documentation</i>
Highline 1100 ECT350	VNLF 082008.4	11.2.2016	OETI	3.- 4.2.2016
Highline 630 ECT350	PF13350	7.7.2010	DBI	
Epoca Twist ECT350	VN710 126599.1	6.2.2017	OETI	
Epoca Silky ECT350	VN710 131600.1	3.8.2017	OETI	18.8.2017
Highline 750 ECT350	VNL710 141653.1	6.8.2018	OETI	17.10.2018
Una Tempo Stripe ECT350	VNLF 082008.4	11.2.2016	OETI	3.- 4.2.2016
Ege Tuft 950 ECT350	VNLF 082008.4	11.2.2016	OETI	18.2.2016
Ege Tuft 440 ECT350	VN710 198322.2	15.3.2022	OETI	20.4.2022
Contra Stripe ECT350	VNLF 083483.1	6/2016	OETI	4.2.2016
Epoca Nordic ECT350	VN710 126599.1	6.2.2017	OETI	4.2.2016
Epoca Classic ECT350	VN710 126599.1	6.2.2017	OETI	
Highline Loop ECT350	VN710 126599.1	6.2.2017	OETI	
Una Tempo ECT350	VN710 126599.1	6.2.2017	OETI	
Highline Carré 440 ECT350	VN710 198322.1	15.3.2022	OETI	
Una Crystalline ECT350	VNLF 082008.1	11.2.2016	OETI	4.2.2016
Tinta ECT350	VNLF 082008.1	11.2.2016	OETI	
Una Mikado ECT350	VNL710 130201.1	26.6.2017	OETI	18.8.2017
Una Mineral ECT350	VNL710 144699.1	20.9.2018	OETI	8.11.2018
Una Grano ECT350	VN710 122775.1	12.10.2016	OETI	10.1.2017
ReForm Calico ECT350	VN710 172386.1	26.08.2019	OETI	3.9.2020
Ege Tuft 650 ECT350	VNL710 137253.2	19.2.2018	OETI	
Una Micro Stripe ECT350	VN710 126599.1	6.2.2017	OETI	4.2.2016
Rawline Scala ECT350	VN710 123822.3	19.12.2016	OETI	
Epoca Rustic ECT350	VNL710 130175.1	22.6.2017	OETI	18.8.2018
Una Micro ECT350	VN710 156429.1	4.10.2019	OETI	4.2.2016
Una Brick ECT350	VN710 194233.1	24.02.2022	OETI	20.4.2022
Eco Knit ECT350	VN710 194676.1	03.02.2022	OETI	20.4.2022
Eco Profile ECT350				
Eco Rustic ECT350				

SCOPE:**Group 5B - PA-ECT350 (100% Polyamide / Felt – Ecotrust 350)**

Group 5.1 (PA-ECT350)		Tufted	Cut Pile
Class B_n – s1			
<i>Total weight</i>	2 600 – 3 800 g.m ⁻²	<i>Total thickness</i>	8 – 14,4 mm
<i>Pile weight</i>	630 – 1 500 g.m ⁻²	<i>Pile thickness</i>	4 – 9,2 mm
<i>Classification report</i>	VN710 194233.5 (02.03.2023)	<i>Classification</i>	EN 13501-1
<i>Products in group</i>	Highline 1100 ECT350 Epoca Twist ECT350 Highline 750 ECT350 Highline 630 ECT350 Epoca Silky ECT350		

Group 5.2 (PA-ECT350)		Tufted	Loop Pile
Class B_n – s1			
<i>Total weight</i>	2 400 – 3 500 g.m ⁻²	<i>Total thickness</i>	6,2 - 9,8 mm
<i>Pile weight</i>	440 – 950 g.m ⁻²	<i>Pile thickness</i>	2,0 - 6 mm
<i>Classification report</i>	VN710 194233.5 (02.03.2023)	<i>Classification</i>	EN 13501-1
<i>Products in group</i>	Una Tempo Stripe ECT350 Highline Loop ECT350 Ege Tuft 950 ECT350 Highline Carré ECT350 Ege Tuft 440 ECT350 Una Tempo ECT350 Contra Stripe ECT350 Una Crystalline ECT350 Epoca Classic ECT350 Tinta ECT350 Epoca Nordic ECT350 Una Grano ECT350 Una Mikado ECT350 Ege Tuft 650 ECT 350 Una Mineral ECT350 ReForm Calico ECT 350		

Group 5.3 (PA-ECT350)		Woven	Loop Pile
Class B_n – s1			
<i>Total weight</i>	2 175 – 2 675 g.m ⁻²	<i>Total thickness</i>	4,0 – 5,5 mm
<i>Pile weight</i>	280 – 625 g.m ⁻²	<i>Pile thickness</i>	-
<i>Classification report</i>	VN710 194233.5 (02.03.2023)	<i>Classification</i>	EN 13501-1
<i>Products in group</i>	Eco Knit ECT350 Una Micro Stripe ECT350 Eco Profile ECT350 Una Brick ECT350 Eco Rustic ECT350 Una Micro ECT350 Epoca Rustic ECT350 Rawline Scala ECT350		

Field of application	Horizontal laid floor coverings in form of tiles . The carpet is to be mounted on a substrate of Euroclass A1 _n or A2 _n with a density of at least 1350 kg.m ⁻³ . It is declared for installation with a polyacrylat - copolymer dispersion adhesive (Ege modular tackifier) or similar and for installation with "Eco Pad" fixation. Subgroup 5.2 is used with SBR or PVB for precoating and glue for secondary backing.
-----------------------------	---

